

	1	2	3	4	5	6	7																																																																		
A																																																																									
B																																																																									
C	<table><tr><th colspan="4">Specification</th></tr><tr><td>MIC</td><td>最大像面</td><td>Ø11</td><td>2/3"</td></tr><tr><td rowspan="2">EFL</td><td rowspan="2">焦距</td><td>13.18mm±0.20mm</td><td>At MOD</td></tr><tr><td>12.00mm±0.20mm</td><td>At INF</td></tr><tr><td>BFL</td><td>光学后焦</td><td>8.60mm±0.20mm</td><td>Include CG</td></tr><tr><td>Flange Distance</td><td>法兰距</td><td>17.526mm</td><td>In Air</td></tr><tr><td rowspan="2">TTL</td><td rowspan="2">光学总长</td><td>60.00mm±0.20mm</td><td>At MOD</td></tr><tr><td>56.66mm±0.20mm</td><td>At INF</td></tr><tr><td>FNo</td><td>光圈</td><td>F2.8~F16</td><td></td></tr><tr><td>MOD</td><td>近摄距</td><td>0.15m</td><td></td></tr><tr><td rowspan="2">TV Distortion</td><td rowspan="2">TV畸变</td><td>-0.4607%(Max)</td><td>At MOD</td></tr><tr><td>-0.2451%(Max)</td><td>At 0.5m</td></tr><tr><td>RI</td><td>相对照度</td><td>89.74%</td><td>At the edge of the max circle</td></tr><tr><td>Struct</td><td>光学结构</td><td>2groups,9elements</td><td></td></tr><tr><td>Filter Size</td><td>滤镜尺寸</td><td>M27XP0.5</td><td></td></tr><tr><td>Mount</td><td>接口</td><td>C Mount</td><td></td></tr><tr><td rowspan="3">F</td><td rowspan="3">FOV 视场角</td><td>2/3"</td><td>49.2°x40.3°x30.8°</td></tr><tr><td>1/2"</td><td>36.9°x29.9°x22.7°</td></tr><tr><td>1/3"</td><td>28.1°x22.7°x17.1°</td></tr></table>			Specification				MIC	最大像面	Ø11	2/3"	EFL	焦距	13.18mm±0.20mm	At MOD	12.00mm±0.20mm	At INF	BFL	光学后焦	8.60mm±0.20mm	Include CG	Flange Distance	法兰距	17.526mm	In Air	TTL	光学总长	60.00mm±0.20mm	At MOD	56.66mm±0.20mm	At INF	FNo	光圈	F2.8~F16		MOD	近摄距	0.15m		TV Distortion	TV畸变	-0.4607%(Max)	At MOD	-0.2451%(Max)	At 0.5m	RI	相对照度	89.74%	At the edge of the max circle	Struct	光学结构	2groups,9elements		Filter Size	滤镜尺寸	M27XP0.5		Mount	接口	C Mount		F	FOV 视场角	2/3"	49.2°x40.3°x30.8°	1/2"	36.9°x29.9°x22.7°	1/3"	28.1°x22.7°x17.1°				
Specification																																																																									
MIC	最大像面	Ø11	2/3"																																																																						
EFL	焦距	13.18mm±0.20mm	At MOD																																																																						
		12.00mm±0.20mm	At INF																																																																						
BFL	光学后焦	8.60mm±0.20mm	Include CG																																																																						
Flange Distance	法兰距	17.526mm	In Air																																																																						
TTL	光学总长	60.00mm±0.20mm	At MOD																																																																						
		56.66mm±0.20mm	At INF																																																																						
FNo	光圈	F2.8~F16																																																																							
MOD	近摄距	0.15m																																																																							
TV Distortion	TV畸变	-0.4607%(Max)	At MOD																																																																						
		-0.2451%(Max)	At 0.5m																																																																						
RI	相对照度	89.74%	At the edge of the max circle																																																																						
Struct	光学结构	2groups,9elements																																																																							
Filter Size	滤镜尺寸	M27XP0.5																																																																							
Mount	接口	C Mount																																																																							
F	FOV 视场角	2/3"	49.2°x40.3°x30.8°																																																																						
		1/2"	36.9°x29.9°x22.7°																																																																						
		1/3"	28.1°x22.7°x17.1°																																																																						
D																																																																									
E	<table><tr><th colspan="6">图面名称</th><th colspan="2">12mm工业镜头规格书</th></tr><tr><td colspan="6">机种名称</td><td colspan="2">FA1228-23A02</td></tr><tr><td colspan="6">材料</td><td>/</td><td>版本</td><td>V0</td></tr><tr><td colspan="6">表面处理</td><td>/</td><td>比例</td><td>1:1</td></tr><tr><td colspan="6">单位</td><td>mm</td><td>页次</td><td>1/1</td></tr><tr><td colspan="6">视图</td><td colspan="3"></td></tr></table>							图面名称						12mm工业镜头规格书		机种名称						FA1228-23A02		材料						/	版本	V0	表面处理						/	比例	1:1	单位						mm	页次	1/1	视图																						
图面名称						12mm工业镜头规格书																																																																			
机种名称						FA1228-23A02																																																																			
材料						/	版本	V0																																																																	
表面处理						/	比例	1:1																																																																	
单位						mm	页次	1/1																																																																	
视图																																																																									
F	<table><tr><th>标记</th><th>处数</th><th>变更内容/原因</th><th>担当</th><th>变更日期</th><th>批准</th><th colspan="3"></th></tr><tr><td colspan="9"></td></tr></table>							标记	处数	变更内容/原因	担当	变更日期	批准																																																												
标记	处数	变更内容/原因	担当	变更日期	批准																																																																				